

541,570

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



10/541570




(43) International Publication Date
29 July 2004 (29.07.2004)

PCT

(10) International Publication Number
WO 2004/062946 A1

- (51) International Patent Classification⁷: **B60B 7/20** [GB/GB]; Farmhouse Flat 2, Wallange Paddocks, Coal Pit Lane, Stanthorne, Middlewich CW10 0NB (GB).
- (21) International Application Number: PCT/GB2004/000030
- (22) International Filing Date: 8 January 2004 (08.01.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0300553.5 10 January 2003 (10.01.2003) GB
- (71) Applicant (for all designated States except US): **BENTLEY MOTORS LIMITED** [GB/GB]; Pym's Lane, Crewe, Cheshire CW1 3PL (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **CANNON, Shane**
- (74) Agents: **DOWNEY, William, Gerrard et al.**; Wilson Gunn M'caw, 5th Floor, Blackfriars House, The Parsonage, Manchester, M3 2JA (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
- [Continued on next page]

(54) Title: APPARATUS FOR MAINTAINING THE ORIENTATION OF A BADGE OR OTHER INSIGNIA



(57) Abstract: Apparatus for maintaining the orientation of a badge 6 comprises a housing (1) which is a snap fit in a vehicle wheel (2). The badge 6 is mounted on a support (7) which comprises an axle (8) mounted on bearings (4) and (5) and a counterweight (9). The counterweight creates an off axis centre of gravity which provides a force to maintain the correct orientation of the badge. Movement is damped to prevent excessive oscillation. Damping may be frictional, fluid, air or magnetic. In a modification a centrifugal clutch may be provided to restrain oscillation. In a further modification the position of the badge may be electronically controlled.

WO 2004/062946 A1



Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GE, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Apparatus for maintaining the orientation of a badge or other insignia

The present invention relates to apparatus for maintaining the orientation of a badge or other insignia on a rotatable member. The apparatus is particularly, but not
5 exclusively, intended for maintaining the orientation of a badge or other insignia in the hub of a vehicle wheel during rotation of the wheel.

Arrangement of this general nature are already known. In one such arrangement described in US 2002/0125762A1 a coupler is provided for connection to a vehicle wheel hub. In one form the coupler includes a threaded stud detachably
10 engageable with the internal threads of a mating threaded bore in the hub. This leads to a complicated and expensive arrangement which is difficult to construct and which may be prone to failure. It is an object of the present invention to mitigate these disadvantages.

According to the present invention there is provided apparatus for maintaining
15 the orientation of a badge or other insignia on a rotatable member comprising a housing adapted for attachment to the rotatable member, bearing means located within the housing, a support mounted in the bearing means and adapted to carry the badge or other insignia and means for urging the support to a datum position with respect to the housing whereby, in operation, the orientation of the support and any badge or
20 other insignia connected to it may be maintained, relative to the housing, as the housing rotates.

In a preferred embodiment of the invention, the housing is moulded from synthetic plastics material and is adapted to be a snap fit in the wheel to which it is, in use, to be connected. For this purpose tabs are provided on the housing. The bearing
25 means advantageously comprises two bearings. The support comprises an axle and

the two bearings are axially spaced along the axle. The badge or other insignia are connected to the support, preferably by means of adhesive. The bearings are retained on the axle by means of a retainer. The retainer preferably comprises a star washer advantageously made of spring steel. The means for urging the support comprises a counterweight which advantageously forms an integral part of the support. The counterweight provides a centre of gravity which is radially off axis and is hung in a manner which both avoids applying a bending movement to the bearings and also loads each of the two bearings equally. A lens is positioned closely adjacent the badge and other insignia. It is sealed to the housing. An end cap closes off the housing on the side remote from the lens. The lens and end cap together with the housing form a sealed assembly.

The invention also comprises a vehicle wheel having an assembly as defined above.

In order that the invention may be more clearly understood, one embodiment thereof will now be described by way of example with reference to the accompanying drawings in which:-

Figure 1 shows a cross-section through a badge assembly for a vehicle wheel

Figure 2 shows an exploded isometric view of the badge assembly of Figure 1,

Figure 3 shows a diagrammatic cross-section of a bearing forming part of the assembly of Figures 1 and 2,

Figure 4 shows a diagrammatic cross-section of a modification of the assembly shown in Figures 1 and 2,

- Figure 5 shows a diagrammatic cross-section of another modification of the assembly shown in Figures 1 and 2,
- Figures 5a and 5b respectively show diagrammatic front elevational views of part of the modification of Figure 5 for two different operational conditions,
- Figure 6 shows a diagrammatic cross-section of a further modification of the assembly shown in Figures 1 and 2,
- Figures 6a and 6b respectively show diagrammatic front elevational views of part of the modification of Figure 6 for two different operational conditions,
- Figure 7 shows a diagrammatic cross-section of a further modification of the assembly shown in Figures 1 and 2,
- Figure 7a diagrammatically shows a front elevational view of part of the modification of Figure 7 and,
- Figure 8 shows a diagrammatic cross-section of a still further modification of the assembly of Figures 1 and 2

Referring to the figures, the assembly comprises a housing 1 which is moulded from a heat resistant synthetic plastics material and is a snap fit in the vehicle wheel 2. Tabs 15 are provided for this purpose on the housing 1. No tools are needed to fix the housing 1 in the vehicle wheel 2. This arrangement and material permits repeated removal and refitting of the assembly without reduction in function. The housing 1 comprises an annular formation 3 which supports two rows of bearings 4 and 5 spaced away from each other and concentrically mounted in the formation 3. The assembly also comprises a badge 6 mounted on a support 7. The support 7 comprises an axle 8 which is mounted in the bearings 4 and 5 and a counterweight 9. The badge 6 is made

of an ultra-violet (UV) resistant material. The axle 8 is retained within the two rows of bearings 4 and 5 and the bearings 4 and 5 within the housing 1 by means of a concentrically mounted steel washer 10 and a steel star washer 11. The washer 10 provides a suitable bearing surface for washer 11. On the inner side of the wheel 2 the housing 1 closed off by means of an end cap 12 moulded from the synthetic plastic material.

The badge 6, which is made of ultraviolet (UV) resistant material, is fixed to the support 7 by means of adhesive. A thin lens 13 made of a scratchproof, compact and ultra violet (UV) resistant transparent material is mounted on the housing 1 very close to the badge 6 to avoid optical distortion. The counterweight 9 is shaped so that the centre of gravity of the entire rotating assembly is positioned between the midpoint of the two rows of bearings 4 and 5. The counterweight design ensures correct orientation. The counterweight 9 creates a centre of gravity that is radially off axis. This off axis centre of gravity provides the force to maintain the correct orientation of the visible badge. The counterweight is under hung in a manner that both avoids applying a bending movement to the bearings 4 and 5 and also loads each bearing equally. The lens 13 and end cap 8 provide a fully sealed assembly preventing ingress of debris and moisture into the rotating parts of the assembly which would adversely affect operation. The star washer 11 provides location and a small residual retention force to stop end play of the axle 8 relative to the housing 1. This is important because of the close proximity of the lens 13 to the badge 6 which in turn is necessary to reduce optical distortion. The double row bearing constrains angular movement of the badge, important because of the close proximity to the lens 13. Very slight damping is also present in the mechanism, both to avoid a long period of badge oscillation when the vehicle comes to rest and to prevent excessive

oscillation due to normal road inputs occurring during driving. The damping function is friction based, the friction source being the seals on the bearings.

Referring to Figure 3, which diagrammatically shows a cross-section through a bearing, this friction damping may be adjusted and adjustment may be achieved in different ways. The bearing comprises inner and outer races 30 and 31 between which ball bearings 34 are constrained. Grease 33 surrounds the ball bearings and seals 32 are disposed between the races 30 and 31 to prevent leakage of grease. By increasing the tightness of the seals, the friction may be increased. Alternatively, or in addition, the viscosity of the grease may be varied. The thicker the grease the higher the friction. In another alternative, the assembly may be preloaded, the higher the preload, the greater the friction. Larger diameter balls (for example 0.05mm) create more preload if the other bearing race dimensions remain constant. High friction provides correspondingly high damping. This tends to promote rotation of the badge with the wheel at high speed, but very little oscillatory motion of the badge just after the vehicle comes to rest. Low friction provides corresponding low damping. This may mean that the badge does not rotate with the wheel at high speeds but also that there is oscillatory motion of the badge just after the vehicle comes to rest.

Although two rows of bearings have been described a single row of bearings may be used if desired. Indeed, various bearing arrangements are possible provided they offer the necessary support. Thus plain, single row (as shown in Figure 4) or double row (as shown in Figure 1) bearings may be used. Similarly different shapes of bearing elements may be used such as ball or roller. In Figure 4 the bearing is referenced 40, the housing 41 and the axle mounted in the bearing 42.

Referring to Figures 5, 5a and 5b a modification is shown in which a centrifugal clutch is provided. As previously the badge is mounted on a support 57

which in turn is mounted through an axle 58 in a bearing 50. The possibility exists that due to forces applied during normal driving, the counterweighted axle 58 may rotate with the vehicle wheel and may continue to rotate, when the vehicle comes to rest. The clutch comprises a plate 52 connected to counterweight 53 by a spring 54.

5 If the axle rotates centrifugal forces urges the plate out into contact with housing 51. Any tendency of the axle 58 and support 57 to continue to rotate as the vehicle wheel comes to rest is restrained by this contact. The spring withdraws the plate and breaks the contact as the vehicle wheel comes to rest when the axle support and badge may return to the datum position. Figure 5b shows the clutch in a first operative condition

10 with the plate 52 in contact with the housing 51 and Figure 5a shows the clutch in a second operative condition with the plate 52 not in contact with the housing 51 and the axle permitted to return to the datum position. In other respects the arrangement is as shown in Figures 1 and 2.

Referring to Figures 6, 6a and 6b, a modification is shown in which rotational

15 speed sensitive fluid damping is provided. To this end radially extending vanes 62 are mounted on axle 68 within a sealed chamber 65 formed by sealing off part of housing 61 by means of a seal 64. The chamber 65 is partially filled with viscous fluid 69. When the vehicle is static a predetermined portion of the vanes 62 is submersed in the fluid. This is the maximum damping case. As the vehicle speed

20 increases centrifugal force tends to distribute the fluid more evenly around the circumference of the chamber, which reduces the contact between the vanes and the fluid, reducing damping. The amount of fluid and the shape of both the chamber and the vanes can be adjusted to give the correct speed/damping relationship. Ideally the damping should be less at high speeds, to prevent significant canting over of the

25 badge and support 67. In other respects the arrangement is the same as the previous

embodiment's axle 68 being mounted in bearing 60 and a counterweight 63 being provided on the axle 68.

Referring to Figures 7 and 7a a modification is shown in which air damping is provided. A plurality of vanes 72 are provided, for example by moulding, on the
5 inner surface of housing 71. A further series of vanes 73 are mounted on axle 78. All vanes extend radially and vanes of the two series are disposed in close proximity to each other. The close proximity of the housing vanes 72 and the axle vanes 73 and air viscosity create a damping effect. The form and proximity of both sets of vanes can be altered by design to achieve the required damping characteristics. The vanes could
10 also distort due to centrifugal force, thereby altering the gap and, affecting damping. This is another tuneable element. In other respects the arrangement is the same as the previous embodiments axle 78 being mounted in bearing 70 and a counterweight 75 and support 77 being mounted on axle 78.

Referring to Figure 8, a modification is shown in which magnetic damping is
15 provided. For this purpose a magnet 82 is mounted on a non-rotating part of the vehicle and a magnetic plate 83 on support 87. The magnetic attraction between magnet 82 and plate 83 provides the required damping and controls the orientation of the support 87 and badge supported on it. In other respects the arrangement is the same as previous embodiments axle 88 being mounted in bearing 80.

20 It would also be possible to control the position of the badge electronically by means of a feedback arrangement in which deviation from a desired datum position is used to produce a signal which is fed back and used to return the badge to the datum position. A stepper motor or other appropriate means could be used to index the badge.

The above described arrangements are designed to be maintenance free. All parts are physically and dimensionally stable for the operating conditions encountered so that the assembly remains functional over the life of the vehicle. Each assembly
5 can also be retro fitted to existing vehicle wheel designs without modification of those designs.

It will be appreciated that the above embodiments has been described, by way of example only and that many variations are possible without departing from the invention.

10

15

20

25

CLAIMS

1. Apparatus for maintaining the orientation of a badge or other insignia on a rotatable member comprising a housing adapted for attachment to the rotatable member, bearing means located within the housing, a support mounted in the bearing means and adapted to carry the badge or other insignia and means for urging the support to a datum position with respect to the housing whereby, in operation, the orientation of the support and any badge or other insignia connected to it may be maintained, relative to the housing, as the housing rotates.
2. Apparatus as claimed in claim 1, in which the housing is moulded from synthetic plastics material.
3. Apparatus as claimed in claim 1 or 2, in which the housing is adapted to be a snap fit in the rotatable member in which it is, in use, to be connected.
4. Apparatus as claimed in claim 3, in which tabs are provided on the housing to enable the snap fit.
5. Apparatus as claimed in any preceding claims, in which the bearing means comprises two bearings.
6. Apparatus as claimed in claim 5, in which the support comprises an axle and the two bearings are axially spaced along the axle.
7. Apparatus as claimed in claim 6, in which the bearings are retained on the axle by means of a retainer.
8. Apparatus as claimed in claim 7, in which the retainer comprises a star washer.
9. Apparatus as claimed in claim 7, 8 or 9, in which the star washer is made of spring steel.


10. Apparatus as claimed in any preceding claim, in which the badge or other insignia are connected to the support.
11. Apparatus as claimed in claim 10, in which the badge or other insignia are connected to the support by means of adhesive.
- 5 12. Apparatus as claimed in any preceding claim, in which the means for urging the support comprises a counterweight.
13. Apparatus as claimed in claim 12, in which the counterweight forms an integral part of the support.
14. Apparatus as claimed in claim 12 or 13, when appendant directly or indirectly
10 to claim 5, in which the counterweight provides a centre of gravity which is radially off axis and is hung in a manner which both avoids applying a bending movement to the bearings and also loads each of the two bearings equally.
15. Apparatus as claimed in any preceding claim, in which a lens is positioned
15 closely adjacent to the badge or other insignia.
16. Apparatus as claimed in claim 15, in which the lens is sealer in a housing.
17. Apparatus as claimed in claim 15 or 16, in which an end cap closes off the housing on the side remote from the lens.
18. Apparatus as claimed in claim 17, in which the lens and end cap together form
20 a sealed assembly.
19. Apparatus as claimed in any preceding claim, in which damping means are provided to resist oscillation of the badge or other insignia.
20. Apparatus as claimed in claim 19, in which the damping is friction based.
21. Apparatus as claimed in claim 20, in which the friction is provided by seals or
25 the bearing means.

22. Apparatus as claimed in claim 21, in which the friction damping is adjustable.
23. Apparatus as claimed in claim 19, in which the dampings means comprises a centrifugal clutch.
24. Apparatus as claimed in claim 19, in which the damping means comprises speed sensitive fluid damping.
25. Apparatus as claimed in claim 19, in which the damping means is magnetic.
26. Apparatus as claimed in claim 19, in which the damping means is air damping.
27. Apparatus as claimed in claim 1, in which the means for urging the support to a datum position are electronic.
28. Apparatus as claimed in claim 27, in which the electronic means comprises a stepper motor operative to respond to a feedback signal to return the badge or other insignia to the datum position.
29. A vehicle wheel comprising apparatus as claimed in any preceding claim.

15

20

25






Fig. 2




FIG. 3







FIG. 4

**Fig. 5****Fig. 5a****Fig. 5b**




Fig. 6




Fig. 6a







Fig. 6b



INTERNATIONAL SEARCH REPORT

National Application No
PCT/GB2004/000030

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B60B7/20

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B60B G01F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X Y	EP 1 106 389 A (SHINSEI CO LTD) 13 June 2001 (2001-06-13) column 2, line 29 - line 37 column 5, line 44 - column 6, line 23 column 9, line 11 - line 15 column 9, line 47 - line 55 figures 1a,5	1-5,10, 12,29 6,7, 13-15, 19-21,24
X Y	PATENT ABSTRACTS OF JAPAN vol. 2000, no. 20, 10 July 2001 (2001-07-10) -& JP 2001 063302 A (MATSUURA MINEO), 13 March 2001 (2001-03-13) abstract	1,5-7, 10,12, 14,29 8,9,27

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the International filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the International filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

7 May 2004

Date of mailing of the international search report

17/05/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Verkerk, E

INTERNATIONAL SEARCH REPORT--

International Application No
PCT/GB2004/000030

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	DE 89 08 995 U (JENSEN JENS) 26 October 1989 (1989-10-26) page 3, paragraph 4 - page 4, paragraph 1 figure 3	6,7,13, 14
Y	GB 2 214 684 A (GILDERDALE ANDREW; GILDERDALE IAN; GILDERDALE KENNETH; GILDERDALE STEP) 6 September 1989 (1989-09-06) the whole document	8,9
Y	US 5 316 376 A (DEFREITAS MANUEL P) 31 May 1994 (1994-05-31) column 3, line 18 - line 27 abstract; figure 11	15
Y	US 5 659 989 A (HSIAO LESLIE ET AL) 26 August 1997 (1997-08-26) column 10, line 1 - line 6 column 10, line 32 - line 53 column 11, line 4 - line 10 figures 19,21	19-21
Y	US 4 280 293 A (KOVLENKO EUGENE N ET AL) 28 July 1981 (1981-07-28) column 1, line 61 - column 2, line 9 figures 2,3	19,24
Y	US 5 190 354 A (LEVY SERGE ET AL) 2 March 1993 (1993-03-02) column 5, line 33 - line 45; figure 8	27
A	US 5 957 542 A (BOOTHE RALPH T ET AL) 28 September 1999 (1999-09-28) column 4, line 44 - line 47 figure 1A	17
A	WO 02/32694 A (LITZKA BERND) 25 April 2002 (2002-04-25) page 6, line 12 - line 16	23

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB2004/000030

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1106389	A	13-06-2001	JP 3126124 B2	22-01-2001
			JP 2001158201 A	12-06-2001
			JP 2001277802 A	10-10-2001
			EP 1106389 A1	13-06-2001
			US 2002125761 A1	12-09-2002
JP 2001063302	A	13-03-2001	NONE	
DE 8908995	U	26-10-1989	DE 8908995 U1	26-10-1989
GB 2214684	A	06-09-1989	NONE	
US 5316376	A	31-05-1994	NONE	
US 5659989	A	26-08-1997	US 5623777 A	29-04-1997
			US 5490342 A	13-02-1996
US 4280293	A	28-07-1981	NONE	
US 5190354	A	02-03-1993	NONE	
US 5957542	A	28-09-1999	CA 2292435 A1	03-12-1998
			EP 0983153 A1	08-03-2000
			JP 2002501460 T	15-01-2002
			WO 9854005 A1	03-12-1998
WO 0232694	A	25-04-2002	AT 411042 B	25-09-2003
			WO 0232694 A1	25-04-2002
			AT 12072001 A	15-02-2003
			AU 9346601 A	29-04-2002
			CA 2426053 A1	16-04-2003
			EP 1328410 A1	23-07-2003

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.